



## ECOTHERM

### Effective cleaning with hot water.

The hot water unit EcoTherm reaches performance levels, which otherwise are only achieved by bigger high-pressure systems. Cleaning with hot water is often more effective than with cold water. This means that lower pressures are sufficient for comparable cleaning tasks.

**Advantages at a glance:**

- The extremely reliable and durable high-pressure pump 70Y is characterised by its compact design and low weight.
- Economical and robust diesel engine (38 kW).
- The unit and the heater are operated via a common, modern and intuitive control.  
(For detailed information on our device controls, see page 16 onwards).
- The compact and weight-optimised single-axle trailer is approved as a trailer up to 80 km/h and can be brought to site with almost any middle-class car.
- With up to 95 °C facades, small pipes, industrial flooring and other surfaces can be easily cleaned, oil and grease can be washed away and coating can be removed.
- The tank system with five chambers including a safety trough prevents the leakage of fluids such as fuel, oil or softeners.
- Automatic shutdown of the heating elements when there is no water supply increases safety and saves energy costs.
- Maximum safety for the user: The system is pressure free as long as the high-pressure gun is not activated.
- Integrated frost protection technology.

**Technical Data EcoTherm**

Unit type	ET 600	ET 800
Max. pressure bar	600	800
Max. volume flow in l/min	28	21
Max. water temperature in °C		95
Heating oil tank in l		100
Fuel tank in l		100
Water tank in l		200
Weight incl. operating material in kg		1,700
Measures in mm (L x W x H)	4,100 x 1,900 x 1,960	

**1** Graffiti and layers of paint can be easily removed from walls and facades with hot water.

**2** Soiled floors and surfaces can be cleaned by using the EcoTherm.

**3** Working with hot water can be carried out faster, more thoroughly and more economically.

